



Date: May 9th, 2016  
NEW PRODUCT RELEASE  
Tsunami 240 SCFM Filtration

For the unexpected surges ordinary filters cannot handle, Tsunami offers maximum protection to accommodate any application.

What separates Tsunami from other manufacturers is that our filters are machined from 6061 aluminum and are anodized for maximum corrosion resistance, inside and out. This prevents rust and other corrosion from forming inside the filter housings unlike filters manufactured out of die cast materials. Tsunami filtration systems are available in up to three stage packages include water separators, oil coalescing filters and activated carbon filters.

### Water Separators

Part Number	(scfm) Max Flow	Port Size	Drain
21999-0850	240	2"	Float
21999-0850-ED	240	2"	Electronic
21999-0850-MM	240	2"	Pneumatic

### Oil Coalescing Filters

Part Number	(scfm) Max Flow	Port Size	Drain
21999-0850-Z-FD	240	2"	Float
21999-0850-Z-ED	240	2"	Electronic
21999-0850-Z-MM	240	2"	Pneumatic

For additional assistance or to place orders please contact customer service at 1.800.782.5752 or submit purchase orders to [orders@gosuburban.com](mailto:orders@gosuburban.com)

### Specifications

- 1 Water separator removes water up to 1 quart per minute & filters particulate down to 10 micron.
- 2 Oil coalescing filter removes oil aerosols down to .001 ppm & traps particulates down to .01 micron.
- 3 Activated carbon filter removes oil vapor down to .003 ppm, removing odor & taste from the air.

### 240 Series Filtration

Maximum Flow: 240 scfm  
Maximum Pressure: 250 psi  
Port Size: 2" NPT  
Maximum Temperature: 175° F

