

NEW PRODUCT

Perfect Solution for Point of Use
Spray Applications



20 Series Membrane Dryer 21999-0892

The 20 Series Membrane Dryer uses proven Tsunami technology to provide your compressed air system with clean, dry air for point of use spray applications.

OPERATION

Incoming contaminated air passes through a stainless steel ball valve before entering the first stage Tsunami Water Separator where water and particulates are removed down to 10 micron. The air then travels through a second stage oil coalescing filter where oil aerosols are filtered down to .001 ppm and particulates are trapped down to .01 micron. The pre-treated air then enters the Membrane Dryer before passing through an outlet regulator.

FEATURES AND BENEFITS

- 100% duty cycle
- No electricity required
- Micro-flex element capacity 3X larger than competitor's elements
- Easy, low cost maintenance

SPECIFICATIONS

- 3.3 CFM sweep air @ 100psi
- Maximum inlet pressure: 175psi
- Maximum outlet pressure: 60psi
- 100° F maximum inlet air temp
- 20 CFM max inlet flow
- 16.7 CFM max outlet flow



Suburban Manufacturing | 10531 Dalton Ave NE | Monticello, MN 55362

phone: 1.800.782.5752 web: www.tsunami.us.com fax: 763.295.6601 email: info@gosuburban.com