

5601 WRAP SLEEVE

LIGHTWEIGHT, FLEXIBLE, AND LIQUID RESISTANT

5601 has gained great popularity due to its ability to remain extremely flexible in environments between -60° to 250°F. This sleeve is constructed on a 1000 denier Cordura substrate, with a heavy urethane coating creates a super low coefficient to wear & prevents any moisture from penetrating the sleeve. 5601 is the ideal option for wet, abrasive, & articulating applications.

5601 features Military-Spec Extreme Hook & Loop closure, allowing the sleeve to be applied post hose assembly. The proprietary fastener has proven to reduce costs associated to installation or maintenance by up to 70%!

Typical Applications: Agricultural Sprayers, Robotics, Asphalt Machines, Cement Trucks, Garbage Trucks, Air Conditioning & Brewery Lines (Radiant-lined version)

- Remains extremely flexible in high and low temperature applications
- Resists damage from petroleum, salt water, gasoline, and mild chemicals
- Non-breathable cover can increase thermal retention by up to 150% in applications requiring consistent viscosity
- Heavy urethane coating protects hoses in abrasive environments and allows the sleeve to move freely over ridged surfaces
- Cut to length; easily installed or retro fitted

SIZING & ORDERING INFORMATION

5601 WRAP SLEEVE

PART NUMBER	MAX I.D.	CIRCUM
SL-1.0-5601	1.0"	3.14
SL-1.25-5601	1.25"	4.08
SL-1.5-5601	1.5"	4.71
SL-1.75-5601	1.75"	5.65
SL-2.0-5601	2.0"	6.28
SL-2.25-5601	2.25"	7.53
SL-2.5-5601	2.5"	7.85
SL-2.75-5601	2.75"	8.79
SL-3.0-5601	3.0"	9.42

PART NUMBER	MAX I.D.	CIRCUM
SL-3.25-5601	3.25"	10.36
SL-3.5-5601	3.5"	10.99
SL-4.0-5601	4.0"	12.56
SL-4.5-5601	4.5"	14.13
SL-5.0-5601	5.0"	15.70
SL-6.0-5601	6.0"	18.84
SL-7.0-5601	7.0"	21.99
SL-8.0-5601	8.0"	25.13
SL-9.0-5601	9.0"	28.27

PART NUMBER	MAX I.D.	CIRCUM
SL-9.5-5601	9.5"	29.84
SL-10.0-5601	10.0"	31.41
SL-11.0-5601	11.0"	34.55
SL-12.0-5601	12.0"	37.69
SL-13.0-5601	13.0"	40.84
SL-14.0-5601	14.0"	43.98
SL-15.0-5601	15.0"	47.12
SL-16.0-5601	16.0"	50.26

Standard lengths sold in 150' and 50' increments.

Available in:

- Black ● Light gray



Hydraulic cylinders rely on the flexibility of 5601 to prevent contamination to piston rods.



5601 is often used to protect sprayer hoses & lines in wet, abrasive applications.



Radiant-lined 5601 helps maintain chemical viscosity in the spray foam industry.

MATERIAL ATTRIBUTES

- ABRASION RESISTANCE
- PUNCTURE RESISTANCE
- CHEMICAL RESISTANCE
- UV PROTECTION
- NON - WICKING ABILITY
- SPALL / SPARK PROTECTION
- WEIGHT / FLEXIBILITY
- TEMPERATURE RATING

