





RADIANT LINED WRAP SLEEVE

BLACK POLY : RADIANT LINED

Radiant Lined Black Poly provides an economical way to bundle and insulated plumbing components that see little-to-no wear. A light PVC coating helps prevent further damage caused by high UV.

Typical Applications: Vac trucks, control valves

MATERIAL ATTRIBUTES

-  **ABRASION RESISTANCE**
██████████
-  **UV PROTECTION**
██████████
-  **WEIGHT / FLEXIBILITY**
██████████
-  **TEMPERATURE RATING**
██████████

For more information, see page 6.

PART NUMBER	MAX I.D.	CIRCUM
RL-1.5-600P	1.5"	4.71
RL-2.0-600P	2.0"	6.28
RL-2.5-600P	2.5"	7.85
RL-3.0-600P	3.0"	9.42
RL-3.5-600P	3.5"	10.99
RL-4.5-600P	4.5"	14.13
RL-5.5-600P	5.5"	17.27
RL-6.5-600P	6.5"	20.14
RL-7.5-600P	7.5"	23.55

Sold in 150' increments.



Used to insulate critical lines on Vac trucks.







1050 : RADIANT LINED

Radiant Lined 1050 is a great all around choice in temperature-reliant environments where mild abrasion is present.

Typical Applications: Diesel exhaust systems, wash down units

MATERIAL ATTRIBUTES

-  **ABRASION RESISTANCE**
██████████
-  **UV PROTECTION**
██████████
-  **WEIGHT / FLEXIBILITY**
██████████
-  **TEMPERATURE RATING**
██████████

For more information see page 4.

PART NUMBER	MAX I.D.	CIRCUM
RL-1.5-1050	1.5"	4.71
RL-2.0-1050	2.0"	6.28
RL-2.5-1050	2.5"	7.85
RL-3.0-1050	3.0"	9.42
RL-3.5-1050	3.5"	10.99
RL-4.5-1050	4.5"	14.13
RL-5.5-1050	5.5"	17.27
RL-6.5-1050	6.5"	20.14
RL-7.5-1050	7.5"	23.55

Sold in 50' and 150' increments.



Tailored to insulate and protect refuse truck lines.







5601 : RADIANT LINED

Radiant Lined 5601 combines the best of both abrasion resistance and thermal retention technologies. A heavy urethane coating prevents moisture/air penetration and protects in abrasive applications.

Typical Applications: Diesel exhaust systems, wash down units

MATERIAL ATTRIBUTES

-  **ABRASION RESISTANCE**
██████████
-  **UV PROTECTION**
██████████
-  **WEIGHT / FLEXIBILITY**
██████████
-  **TEMPERATURE RATING**
██████████

For more information see page 5.

PART NUMBER	MAX I.D.	CIRCUM
RL-1.5-5601	1.5"	4.71
RL-2.0-5601	2.0"	6.28
RL-2.5-5601	2.5"	7.85
RL-3.0-5601	3.0"	9.42
RL-3.5-5601	3.5"	10.99
RL-4.5-5601	4.5"	14.13
RL-5.5-5601	5.5"	17.27
RL-6.5-5601	6.5"	20.14
RL-7.5-5601	7.5"	23.55

Sold in 50' and 150' increments.



Protects hoses and maintains viscosity in SPF applications.

Available in:

- Black
- Light gray

