

FIRE SLEEVE

HEAT & FLAME PROTECTION

HIGH TEMPERATURE FIBERGLASS

Fire Sleeve's bulk fiberglass base and iron-oxide silicon coating make it the optimal single line solution where molten metal splash, radiant heat, chemicals, and abrasion are present. The tubular style sleeve is designed to withstand continuous heat exposure up to 500°F and intermittent heat of up to 3000°F.

In addition to protecting hoses, cables, and pipes, Fire Sleeve can protect people from incurring scorching burn injuries. Offering both regular knitted and woven aerospace grade, the silicon coating allows the sleeve to remain extremely flexible and moisture resistant in tight radius and outdoor environments.

PRODUCT BENEFITS

- Constructed from high bulk fiberglass
- Easy installation over hoses, cables, tubing, and pipes
- Resistant to molten metal splash, radiant heat, abrasion, moisture, chemicals, vibration, electricity, and corrosive atmosphere



PROTECTION FROM:

- Dust and rail sparks
- Flame and molten metal splash
- Extreme engine temps damaging wires




FOR MORE INFORMATION

Contact Your Parts Supplier or Call 1.800.782.5752

10531 Dalton Ave NE | Monticello, MN 55362 | PYTHONCOVERS.COM

FIRE SLEEVE FOR EXTREME TEMPERATURES



Protection from dust & rail sparks.



Flame & molten metal splash protection



Protect wires from extreme engine temps



TYPICAL APPLICATIONS

- Performance automotive
- Steel work
- Oil rigs
- High temperature cable systems
- High temperature wiring systems
- Exhaust systems

FEATURES & BENEFITS

- Unaffected by hydraulic fluids, lubricants, chemicals, and oils
- Withstands exposure to molten steel, aluminum, and glass
- Designed to protect against occasional flame
- Continuous exposure up to 500°F, intermittent up to 3000°F
- Insulates against energy or temperature loss

SIZING & ORDERING INFORMATION

PART NUMBER	MAX I.D.	PART NUMBER	MAX I.D.
FSA-004	0.25"	FSA-028	1.75"
FSA-006	0.375"	FSA-032	2"
FSA-008	0.5"	FSA-036	2.25"
FSA-010	0.625"	FSA-040	2.5"
FSA-012	0.75"	FSA-044	2.75"
FSA-014	0.875"	FSA-048	3"
FSA-016	1"	FSA-052	3.25"
FSA-018	1.13"	FSA-056	3.5"
FSA-020	1.25"	FSA-060	3.75"
FSA-022	1.375"	FSA-064	4"
FSA-024	1.5"	FSA-072	4.5"
		FSA-080	5"
		FSA-088	5.5"
		FSA-096	6"

AEROSPACE FIRE SLEEVE

- ✓ Texturized, Braided Sleeve
- ✓ Silicone Outer Coating
- ✓ Works continuously from 500°F up to 3000°F with long duration
- ✓ Excellent thermal insulation
- ✓ Excellent molten splash resistance
- ✓ Excellent tearing and tensile strength

STANDARD FIRE SLEEVE

- ✗ Braided Sleeve
- ✓ Silicone Outer Coating
- ✗ Works continuously from 500°F up to 3000°F
- ✗ Good thermal insulation
- ✗ Good molten splash resistance
- ✗ Good tearing and tensile strength

Standard lengths sold in 100' increments.