



WELD ARMOR

Developed by

SUBURBAN  
MANUFACTURING GROUP

# WELD ARMOR

## LEATHER

FOR HIGH ABRASION &  
HIGH HEAT ENVIRONMENTS

### FEATURES

-  ABRASION RESISTANCE  
—————
-  SPARK SPALL / HEAT  
—————
-  LIGHTWEIGHT  
—————
-  EASY INSTALL  
—————
-  EXTEND LIFE  
—————

### TYPICAL APPLICATIONS

• Arc • MIG • TIG • Laser

## WELD WITH CONFIDENCE

Weld cable wraps are essential for operator safety and cable maintenance in welding operations. The Weld Armor Series provides crucial protection for welding equipment from harsh and demanding environments, such as exposure to intense heat, molten metal splatter, sparks, and abrasive debris which can severely damage cables. By installing the Weld Armor cable wrap, you can enhance workplace safety, reduce downtime and lower maintenance costs associated with cable repairs or replacements, and improve the overall efficiency and productivity of welding operations.

### PROTECT YOUR CABLE LEADS

Protect your cable leads from spark, spall, heat, and high abrasion environments with a weld wrap. With five wraps available from our top-of-the-line Leather to our low-cost Canvas, we are sure to have a sleeve that fits your welding environment.

### PRODUCT BENEFITS

- **Flame Retardant:** reduces the risk of fire during regular welding operating
- **Heat Resistant:** protects cable from heat damage and deformation
- **Increase Productivity:** quick and easy application for less downtime
- **Extend Equipment Life:** prolong the life of tools and components



Best for tank, frame, and fixture welding, this welding cable lead cover can be dragged over grates, sharp edges, rough floors, and withstand ambient conditions.

### SIZE & ORDER INFO

| PART NUMBER | DESCRIPTION                          | ROLL LENGTH |
|-------------|--------------------------------------|-------------|
| WA-1.25-L   | Leather Weld Cable / Lead Wrap 1.25" | 75 ft       |
| WA-1.5-L    | Leather Weld Cable / Lead Wrap 1.5"  | 75 ft       |
| WA-2.0-L    | Leather Weld Cable / Lead Wrap 2.0"  | 75 ft       |

75 ft / 1 roll

FEATURING **WELDED  
HOOK AND LOOP** FOR  
STITCH-FREE SECURITY



**PYTHON**  
PROTECTIVE SLEEVE + COVERS

FOR MORE INFORMATION

**Contact Your Parts Supplier or Call 1.800.782.5752**

10531 Dalton Ave NE | Monticello, MN 55362 | PYTHONCOVERS.COM

## FOR HIGH ABRASION ENVIRONMENTS

### NEOPRENE

#### TYPICAL APPLICATIONS

• MIG • TIG • Laser

Best used when there is a medium to low amount of spark and spall, with a max temperature of 250°F.



ABRASION RESISTANCE



SPARK SPALL / HEAT



LIGHTWEIGHT



EASY INSTALL



EXTEND LIFE

#### SIZE & ORDER INFO

| PART NUMBER | DESCRIPTION                           | ROLL LENGTH |
|-------------|---------------------------------------|-------------|
| WA-1.25-N   | Neoprene Weld Cable / Lead Wrap 1.25" | 150 ft      |
| WA-1.5-N    | Neoprene Weld Cable / Lead Wrap 1.5"  | 150 ft      |
| WA-2.0-N    | Neoprene Weld Cable / Lead Wrap 2.0"  | 150 ft      |

150 ft / 1 roll

### CANVAS

#### TYPICAL APPLICATIONS

• MIG • TIG • Laser

Best used where welder leads are suspended and have occasional dragging on the floor, table, or on the application being welded.



ABRASION RESISTANCE



SPARK SPALL / HEAT



LIGHTWEIGHT



EASY INSTALL



EXTEND LIFE

#### SIZE & ORDER INFO

| PART NUMBER | DESCRIPTION                         | ROLL LENGTH |
|-------------|-------------------------------------|-------------|
| WA-1.25-C   | Canvas Weld Cable / Lead Wrap 1.25" | 300 ft      |
| WA-1.5-C    | Canvas Weld Cable / Lead Wrap 1.5"  | 300 ft      |
| WA-2.0-C    | Canvas Weld Cable / Lead Wrap 2.0"  | 300 ft      |

300 ft / 1 roll

## FOR HIGH HEAT ENVIRONMENTS

### ACRYLIC

#### TYPICAL APPLICATIONS

• Arc • MIG • TIG • Laser  
• Plasma Cutter • Robots

Best used in low to no abrasion applications and can last in temperatures up to 1000°F with continual heat exposure.



ABRASION RESISTANCE



SPARK SPALL / HEAT



LIGHTWEIGHT



EASY INSTALL



EXTEND LIFE

#### SIZE & ORDER INFO

| PART NUMBER | DESCRIPTION                                             | ROLL LENGTH |
|-------------|---------------------------------------------------------|-------------|
| WA-1.25-A   | Acrylic Coated Fiber Glass Weld Cable / Lead Wrap 1.25" | 150 ft      |
| WA-1.5-A    | Acrylic Coated Fiber Glass Weld Cable / Lead Wrap 1.5"  | 150 ft      |
| WA-2.0-A    | Acrylic Coated Fiber Glass Weld Cable / Lead Wrap 2.0"  | 150 ft      |

150 ft / 1 roll

### TEFLON

#### TYPICAL APPLICATIONS

• Grind Robots • Weld Robots • Fast Robots  
• Plasma Cutters

Best used in low to no abrasion applications and can last in temperatures up to 600°F with continual heat exposure.



ABRASION RESISTANCE



SPARK SPALL / HEAT



LIGHTWEIGHT



EASY INSTALL



EXTEND LIFE

#### SIZE & ORDER INFO

| PART NUMBER | DESCRIPTION                                            | ROLL LENGTH |
|-------------|--------------------------------------------------------|-------------|
| WA-1.25-T   | Teflon Coated Fiber Glass Weld Cable / Lead Wrap 1.25" | 150 ft      |
| WA-1.5-T    | Teflon Coated Fiber Glass Weld Cable / Lead Wrap 1.5"  | 150 ft      |
| WA-2.0-T    | Teflon Coated Fiber Glass Weld Cable / Lead Wrap 2.0"  | 150 ft      |

150 ft / 1 roll